




电液同步数控板料折弯机 CNC ELECTRO-HYDRAULIC SYNCHRO PRESS BRAKE



双V下模(选配)
Double V die (Option)



偏心式快夹(选配) 螺纹式快夹(选配)
Eccentric fast clamp (Option) Threaded fast clamp (Option)



数控后挡料(选配)
CNC backgauge (Option)



丝杆升降前托料(选配)
Screw lift front material holder (Option)

产品介绍 / Product Introduction

1. 时尚的外观设计, 高刚性、高速度的电液同步数控板料折弯机。
2. 电液伺服系统, 全闭环控制滑块运行精度。
3. 工作台液压挠度补偿, 确保工件加工精度。
4. 后挡料采用伺服电机驱动, 滚珠丝杆传动, 直线导轨导向, 确保定位精度。

1. With stylish design, high rigidity, high speed.
2. Electro-hydraulic servo system, closed loop control system controls accuracy.
3. Worktable adopts hydraulic deflection compensation to ensure the accuracy of the workpiece.
4. Back gauge is driven by servo motor, adopted ball-screw and linear guide way, it could make sure positioning accuracy.



激光保护装置(选配)
Laser protection device (Option)



数控随动托料(选配)
CNC following material holder (Option)

6轴后挡料(选配)
6-axis backgauge (Option)

型号 Model	公称压力 Nominal Pressure (KN)	工作台长度 Length of Table (mm)	立柱间距 Distance between Housings (mm)	喉口深度 Throat Depth (mm)	滑块行程 Stroke (mm)	滑块速度 Ram Speed (mm/s)	最大开启高度 Open Height (mm)	主电机功率 Main Motor (KW)	油箱容积 Volume of oil tank (L)	单机重量 Weight (kg)	单机外形尺寸 Overall Dimensions (L x W x H) (mm)
WE67K-63/2500	630	2500	2050	250	200	110 9 90	460	7.5	300	6000	2770×1895×2480
WE67K-80/2500	800	2500	2050	250	200	110 9 115	460	7.5	300	6200	2770×1900×2480
WE67K-100/3200	1000	3200	2650	320	200	120 10 110	475	7.5	380	8700	3450×1955×2565
WE67K-100/4000	1000	4000	3100	320	200	120 10 110	475	7.5	380	11000	4250×1955×2855
WE67K-125/3200	1250	3200	2650	320	200	100 8.5 75	490	7.5	380	8900	3550×1990×2610
WE67K-125/4000	1250	4000	3100	430	200	100 8.5 75	490	7.5	380	11300	4250×2140×2870
WE67K-160/3200	1600	3200	2650	320	200	100 10 90	500	11	400	11000	3200×2050×2915
WE67K-160/4000	1600	4000	3100	320	200	100 10 90	500	11	400	12300	4080×2050×2915
WE67K-200/3200	2000	3200	2650	320	200	80 8 80	480	15	560	10300	3450×2145×2960
WE67K-200/4000	2000	4000	3100	320	200	80 8 80	480	15	670	11500	4250×2145×2960
WE67K-250/3200	2500	3200	2650	400	250	80 7 70	520	15	560	14500	3410×2300×3065
WE67K-250/4000	2500	4000	3100	400	250	80 7 70	520	15	670	15800	4210×2300×3065
WE67K-250/5000	2500	5000	4000	400	250	80 7 70	520	15	800	18500	5210×2300×4160
WE67K-250/6000	2500	6000	4800	400	250	80 7 70	520	15	1000	21000	6250×2300×4760
WE67K-320/3200	3200	3200	2650	400	250	70 7.5 75	480	22	600	19500	3790×2510×3320
WE67K-320/4000	3200	4000	3100	400	250	70 7.5 75	480	22	720	21000	4590×2510×3320
WE67K-320/5000	3200	5000	4000	400	250	70 7.5 75	480	22	968	24000	5540×2510×3910
WE67K-320/6000	3200	6000	4800	400	250	70 7.5 75	480	22	1187	28500	6100×2560×4560
WE67K-400/3200	4000	3200	2650	500	320	60 7 60	660	30	600	22500	3410×3280×3565
WE67K-400/4000	4000	4000	3100	500	320	60 7 60	660	30	720	24500	4100×3280×3650
WE67K-400/5000	4000	5000	4000	500	320	60 7 60	660	30	968	29500	5100×3280×4600
WE67K-400/6000	4000	6000	4800	500	320	60 7 60	660	30	1187	36500	6150×3280×5300
WE67K-500/4000	5000	4000	3100	600	320	90 9 90	760	45	870	38000	4280×3645×4150
WE67K-500/5000	5000	5000	4000	600	320	90 9 90	760	45	1146	42000	5280×3645×4600
WE67K-500/6000	5000	6000	4800	600	320	90 9 90	760	45	1400	50000	6150×3645×5400
WE67K-600/6000	6000	6000	4800	1000	320	70 7.5 75	960	45	1400	62000	6211×5960×5500
WE67K-800/6000	8000	6000	4800	1100	350	80 8 70	1250	55	2100	89000	6240×7500×6200
WE67K-1000/6000	10000	6000	4800	1400	400	70 8 70	1350	2×45	2100	118000	6240×8080×6600
WE67K-1200/6000	12000	6000	4800	1600	450	70 7 65	1550	2×45	2100	135000	6240×8100×6600
WE67K-1600/6000	16000	6000	4800	1100	450	70 6.5 55	1200	2×55	3900	155000	6240×8133×7050
WE67K-1600/9000	16000	9000	6500	1100	450	70 6.5 55	1200	2×55	3900	177000	9240×8133×8250

本参数若有变更, 恕不另行通知。
Due to continual improvements, specifications are subject to change without notice.